

Lump Sulphur (Specification)

Property	Limits	Test Method
Physical Form	Lumps & Powder	Visual
Appearance	Bright Yellow	Visual
Purity on Dry Basis, wt.%	99.80% Min	ASTM D-4239
Moisture, wt.%	0.02% Max	ASTM D-2790
Ash Content, wt.%	0.015% Max	ASTM D-1509
Organic Solid Matter, wt.%	0.01% Max	NA
Acid Content, wt.%	0.0001% Max	ASTM D-1613
Mechanical Impurities (Paper, Wood, Sand Etc.), wt.%	0.01% Max	NA

Granular Sulphur (Specification)

Property	Limits	Test Method
Physical Form	Granular	Visual
Appearance	Bright Yellow	Visual
Purity on Dry Basis, wt.%	99.80% Min	ASTM D-4239
Ash Content, wt.%	0.05% Max	ASTM D-1509
Acidity, wt.%	0.02% Max	ASTM D-1613
Moisture, wt.%	0.5% Max	ASTM D-2790
Hydrocarbons, wt.%	0.05% Max	ASTM D-2360
Organic Solid Matter, wt.%	0.01% Max	NA
Size Distribution		
- Bigger than 4.75 mm, wt.%	5% Max	
- Between 2.4 and 4.4 mm, wt.%	75% Min	
- Smaller than 2 mm, wt.%	3% Max	
- Smaller than 1.19 mm, wt.%	2% Max	
- Smaller than 300 microns, wt.%	0.1% Max	

Packing - Jumbo Bags (Specification)

Capacity:	1Ton, 1.5Ton, 2.0Ton, 2.5Ton
Materials:	PP woven coated fabric, Pure
Style of Bag:	Circular/Square/Rectangular shape
Color:	White or Beige
Safety factor:	5:1 or 6:1
Top:	Filling Spout/Open/Skirt
Bottom:	Discharge Spout/Flat
Lifting loop:	1/2/3/4pcs